

PN-OWL: A Two-Stage Algorithm to Learn Fuzzy Concept Inclusions Rules from OWL 2 Ontologies

Franco Alberto Cardillo^a, Franca Debole^b, Umberto Straccia^b

^a*Istituto di Linguistica Computazionale, CNR, Pisa, Italy*

^b*Istituto di Scienza e Tecnologie dell'Informazione, CNR, Pisa, Italy*

Abstract

Given a target class T of an OWL 2 ontology and instances of T , we address the problem of learning graded fuzzy class inclusion rules that aim to describe sufficient conditions for being an individual classified as an instance of the class T .

To do so, we present PN-OWL that is a two-stage learning algorithm consisting of a P-stage and an N-stage. In the P-stage, the algorithm learns fuzzy OWL 2 class inclusion rules (the P-rules). These rules aim to cover as many positive examples as possible, increasing *recall*, without compromising too much *precision*. In the N-stage, the algorithm learns fuzzy OWL 2 class inclusion rules (the N-rules), that try to rule out as many false positives, covered by the rules learnt at the P-stage, as possible. Roughly, the P-rules tell why an individual should be classified as an instance of T , while the N-rules tell why it should not.

PN-OWL then aggregates the P-rules and the N-rules by combining them via an aggregation function to allow for a final decision on whether an individual is an instance of T or not.

We also illustrate the effectiveness of PN-OWL through extensive experimentation.

Keywords: OWL 2 Ontologies, Machine Learning, Fuzzy Logic, Concept/Class Inclusion Rules

Email addresses: `francoalberto.cardillo@ilc.cnr.it` (Franco Alberto Cardillo), `franca.debole@isti.cnr.it` (Franca Debole), `umberto.straccia@isti.cnr.it` (Umberto Straccia)

1. Introduction

OWL 2 [1], a W3C standard, is nowadays a quite popular formal language allowing to represent *structured* knowledge. Its formal semantics is based on *Description Logics* (DLs) [2].

The main ingredients of DLs are concept/class descriptions, inheritance relationships among them, and instances of them. *Fuzzy DLs* [3, 4] have been proposed as the natural extension of DLs to mathematical fuzzy logic, while *Fuzzy OWL 2* [5] is a proposed fuzzy extension of OWL 2.

Despite an important amount of work that has been carried out about DLs, the application of machine learning techniques to OWL 2 ontologies is relatively less addressed, especially compared to the *Inductive Logic Programming* (ILP) setting (see *e.g.* [6] for more insights on ILP).

In this work, we focus on the problem of learning fuzzy concept/class inclusion rules from OWL 2 ontologies [7, 8]. Specifically, given a target class T of an OWL 2 ontology and instances of T (the so-called positive examples), we address the problem of learning graded fuzzy class inclusion rules that aim to describe sufficient conditions for being an individual classified as an instance of the class T .

To do so, we propose to rely on an adaptation of the PN-rule algorithm [9, 10] to the fuzzy OWL 2 case. Our algorithm, called PN-OWL, consists of a *P-stage* in which *positive* fuzzy rules (called *P-rules*) are learnt to cover as many as possible instances of the target class (increase *recall*), without compromising too much *precision*, and an *N-stage* in which *negative* fuzzy rules (called *N-rules*) are learnt to rule out as many false positives, covered by the P-stage, as possible. Essentially, the P-rules tell why an individual should be classified as an instance of T , while the N-rules tell why it should not. Then we aggregate the rules learnt at the P-stage and the N-stage by combining them via an aggregation function to allow for a final decision on whether an individual is an instance of T or not.

A feature of our PN-OWL algorithm is that it encodes all learned rules in Fuzzy OWL 2. Consequently, a Fuzzy OWL 2 reasoner can automatically assess the degree to which an individual belongs to the target class T . We will also illustrate the effectiveness of PN-OWL through extensive experimentation on various real-valued OWL 2 ontologies.

The paper is organized as follows. In Section 2, we recap shortly the main concepts and notations we will rely on in this paper. Then, in Section 3 we will present PN-OWL, which is evaluated in Section 4. In Section 5




Fig. 1. (a) triangular function $tri(a, b, c)$, (b) left shoulder function $ls(a, b)$, (c) right shoulder function $rs(a, b)$, and (d) fuzzy sets over centroids.

we compare our work with closely related work appeared so far. Section 6 concludes and points to some topics of further research.

2. Background

For the sake of completeness, we introduce the main notions related to *Fuzzy Sets* and *Fuzzy Description Logics* we will use in this work (for a more in-depth presentation see *e.g.* [3, 4, 11, 12]). The informed reader may skip this section and get back when needed.

Fuzzy Sets basics. A *fuzzy set* A over a finite crisp set X is a function $A: X \rightarrow [0, 1]$, called *fuzzy membership function* of A . Often, fuzzy set operations conform to $(A \cap B)(x) = \min(A(x), B(x))$, $(A \cup B)(x) = \max(A(x), B(x))$ and $\bar{A}(x) = 1 - A(x)$ ($\bar{A}$ is the set complement of A). The *cardinality* of a fuzzy set is defined as $|A| = \sum_{x \in X} A(x)$. The triangular, the left-shoulder, and right-shoulder functions are frequently used to specify membership functions of fuzzy sets (see (a) - (c) in Fig. 1). One easy method to define the membership functions is to uniformly partition the values of an attribute into 3, 5, or 7 fuzzy sets. Another popular approach may consist in using the *c-means* fuzzy clustering algorithm (see, *e.g.* [13]) with 3, 5, or 7 clusters, where the fuzzy membership functions are shaped as triangular or shoulder functions built around the centroids of the clusters [14, 15] (see (d) in Fig. 1).

57 *Fuzzy Description Logics basics.* We recap the fuzzy DL $\mathcal{AL}\mathcal{E}_{@}(\mathbf{D})$, which
 58 extends the fuzzy DL $\mathcal{AL}\mathcal{E}(\mathbf{D})$ with the *aggregated concept* construct in-
 59 dicated with $@$ [16]. $\mathcal{AL}\mathcal{E}_{@}(\mathbf{D})$ is expressive enough to capture the main
 60 ingredients of fuzzy DLs we are going to use here.

61 We start with the notion of *fuzzy concrete domain*, $\mathbf{D} = \langle \Delta^{\mathbf{D}}, \cdot^{\mathbf{D}} \rangle$, where
 62 $\Delta^{\mathbf{D}}$ is a datatype, $\cdot^{\mathbf{D}}$ is a mapping that assigns to each data value an element
 63 of $\Delta^{\mathbf{D}}$, and to every 1-ary datatype predicate $\mathbf{d}$ a 1-ary fuzzy relation over
 64 $\Delta^{\mathbf{D}}$ (*i.e.* $\cdot^{\mathbf{D}}$ maps each datatype predicate to a function from $\Delta^{\mathbf{D}}$ to $[0, 1]$).
 65 Typical data values one may encounter in OWL 2 ontologies are strings,
 66 numbers, dates, and booleans. For instance, in the domain of numbers, typ-
 67 ical datatype predicates $\mathbf{d}$ are characterized by the well-known membership
 68 functions

$$\begin{aligned} \mathbf{d} \rightarrow & \text{ls}(a, b) \mid \text{rs}(a, b) \mid \text{tri}(a, b, c) \mid \text{trz}(a, b, c, d) \\ & \mid \geq_v \mid \leq_v \mid =_v, \end{aligned}$$

69 where additionally $\geq_v$ (resp. $\leq_v$ and $=_v$) corresponds to the crisp set of data
 70 values that are no less than (resp. no greater than and equal to) the value v .

71 *Aggregation Operators.* (AOs) are used to combine different pieces of infor-
 72 mation. Numerous AOs differ on the assumptions of the data (data types)
 73 and the type of information we can incorporate in the model [17]. There is
 74 no standard definition of AO. To what concerns us, an AO of dimension n is
 75 a mapping $@ : [0, 1]^n \rightarrow [0, 1]$. We assume to have a finite family $@_1, \dots, @_l$
 76 of AOs.

77 We are now ready to define $\mathcal{AL}\mathcal{E}_{@}(\mathbf{D})$. So, consider pairwise disjoint
 78 alphabets $\mathbf{I}, \mathbf{A}$ and $\mathbf{R}$, where $\mathbf{I}$ is the set of *individuals*, $\mathbf{A}$ is the set of
 79 *concept names* (also called *atomic concepts* or *class names*) and $\mathbf{R}$ is the set
 80 of *role names*. Each role is either an *object property* r or a *datatype property*
 81 s . The set of *concepts* are built from concept names A, A_i using connectives
 82 and quantification constructs over object properties and datatype properties,
 83 as described by the following syntactic rule ($n_i \geq 1$):

$$\begin{aligned} C \rightarrow & \top \mid \perp \mid A \mid \neg A \mid C_1 \sqcap C_2 \mid \\ & \exists r.C \mid \exists s.\mathbf{d} \mid @_i(A_1, \dots, A_{n_i}). \end{aligned}$$

84 An *ABox* $\mathcal{A}$ consists of a finite set of *assertion* axioms that are expressions
 85 of the form $\langle a:C, \alpha \rangle$ (called *concept assertion*, individual a is an instance
 86 of concept C to degree greater than or equal to $\alpha \in (0, 1]$) or of the form

87 $\langle (a_1, a_2):r, \alpha \rangle$ (called *role assertion*, (a_1, a_2) is an instance of object property
88 r to degree greater than or equal to α), where a_1, a_2 are individuals.
89 A *TBox* $\mathcal{T}$ is a finite set of fuzzy *General Concept Inclusion* (GCI) axioms,
90 where a fuzzy GCI is of the form $\langle C_1 \sqsubseteq C_2, \alpha \rangle$ (C_1 is a sub-concept of C_2
91 to degree greater than or equal to α), where C_i is a concept and $\alpha \in (0, 1]$.
92 We may omit the truth degree α of an axiom, in this case $\alpha = 1$ is assumed
93 and we call the axiom *crisp*. We write $C_1 = C_2$ as a macro for the two GCIs
94 $C_1 \sqsubseteq C_2$ and $C_2 \sqsubseteq C_1$. We may also call a fuzzy GCI of the form $\langle C \sqsubseteq A, \alpha \rangle$,
95 where A is a class name, a *rule*, and C its *body*. A *Knowledge Base* (KB),
96 also called *ontology*, is a pair $\mathcal{K} = \langle \mathcal{T}, \mathcal{A} \rangle$, where $\mathcal{T}$ is a TBox and $\mathcal{A}$ is an
97 ABox. $\text{I}_{\mathcal{K}}$ denotes the set of individuals occurring in $\mathcal{K}$.
98 Concerning the semantics, an interpretation $\mathcal{I}$ maps a concept C into a
99 function $C^{\mathcal{I}}: \Delta^{\mathcal{I}} \rightarrow [0, 1]$ and, thus, an individual belongs to the extension
100 of C to some degree in $[0, 1]$, *i.e.* $C^{\mathcal{I}}$ is a fuzzy set. Specifically, a *fuzzy*
101 *interpretation* is a pair $\mathcal{I} = (\Delta^{\mathcal{I}}, \cdot^{\mathcal{I}})$ consisting of a nonempty (crisp) set
102 $\Delta^{\mathcal{I}}$ (the *domain*) and of a *fuzzy interpretation function* $\cdot^{\mathcal{I}}$ that assigns: (i)
103 to each atomic concept A a function $A^{\mathcal{I}}: \Delta^{\mathcal{I}} \rightarrow [0, 1]$; (ii) to each object
104 property r a function $r^{\mathcal{I}}: \Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}} \rightarrow [0, 1]$; (iii) to each datatype property s
105 a function $s^{\mathcal{I}}: \Delta^{\mathcal{I}} \times \Delta^{\mathbf{D}} \rightarrow [0, 1]$; (iv) to each individual a an element $a^{\mathcal{I}} \in \Delta^{\mathcal{I}}$
106 such that $a^{\mathcal{I}} \neq b^{\mathcal{I}}$ if $a \neq b$ (the so-called *Unique Name Assumption*); and
107 (v) to each data value v an element $v^{\mathcal{I}} \in \Delta^{\mathbf{D}}$. Now, a fuzzy interpretation is
108 extended to concepts as specified below (where $x \in \Delta^{\mathcal{I}}$) [3, 4, 18]:

$$\begin{aligned}
\top^{\mathcal{I}}(x) &= 1 \\
\perp^{\mathcal{I}}(x) &= 0 \\
(C \sqcap D)^{\mathcal{I}}(x) &= \min\{C^{\mathcal{I}}(x), D^{\mathcal{I}}(x)\} \\
(\neg A)^{\mathcal{I}}(x) &= 1 - A^{\mathcal{I}}(x) \\
(\exists r.C)^{\mathcal{I}}(x) &= \sup_{y \in \Delta^{\mathcal{I}}} \{\min\{r^{\mathcal{I}}(x, y), C^{\mathcal{I}}(y)\}\} \\
(\exists s.\mathbf{d})^{\mathcal{I}}(x) &= \sup_{y \in \Delta^{\mathbf{D}}} \{\min\{s^{\mathcal{I}}(x, y), \mathbf{d}^{\mathbf{D}}(y)\}\} \\
(@_i(A_1, \dots, A_{n_i}))^{\mathcal{I}}(x) &= @_i(A_1^{\mathcal{I}}(x), \dots, A_{n_i}^{\mathcal{I}}(x)) .
\end{aligned}$$

109 We will assume that an interpretation is *witnessed*, *i.e.* the supremum is at-
110 tained at some point of the domain [3, 4, 11], *e.g.* $(\exists r.C)^{\mathcal{I}}(x) = \min\{r^{\mathcal{I}}(x, y),$
111 $C^{\mathcal{I}}(y)\}$ for some $y \in \Delta^{\mathcal{I}}$.

112 The *satisfiability of axioms* is then defined by the following conditions: (i)
113 $\mathcal{I}$ satisfies $\langle a:C, \alpha \rangle$ if $C^{\mathcal{I}}(a^{\mathcal{I}}) \geq \alpha$; (ii) $\mathcal{I}$ satisfies $\langle (a, b):r, \alpha \rangle$ if $r^{\mathcal{I}}(a^{\mathcal{I}}, b^{\mathcal{I}}) \geq \alpha$;

114 (iii) $\mathcal{I}$ satisfies $\langle C \sqsubseteq D, \alpha \rangle$ if for all $x \in \Delta^{\mathbf{D}}$, $D(x) \geq C^{\mathcal{I}}(x) \cdot \alpha^{\mathcal{I}}$. $\mathcal{I}$ is a *model*
 115 of $\mathcal{K} = \langle \mathcal{A}, \mathcal{T} \rangle$ iff $\mathcal{I}$ satisfies each axiom in $\mathcal{K}$. If $\mathcal{K}$ has a model we say that
 116 $\mathcal{K}$ is *satisfiable* (or *consistent*).

117 We say that $\mathcal{K}$ *entails* axiom τ , denoted $\mathcal{K} \models \tau$, if every model of $\mathcal{K}$
 118 satisfies τ . The *best entailment degree* of τ of the form $C \sqsubseteq D$, $a:A$ or
 119 $(a,b):R$, denoted $bed(\mathcal{K}, \tau)$, is defined as

$$bed(\mathcal{K}, \tau) = \sup\{\alpha \mid \mathcal{K} \models \langle \tau, \alpha \rangle\} . \quad (1)$$

120 Now, consider concept C , a KB $\mathcal{K}$ and a finite set of individuals $\mathbf{I}$. Then the
 121 *cardinality* of C w.r.t. $\mathcal{K}$ and $\mathbf{I}$, denoted $|C|_{\mathcal{K}}^{\mathbf{I}}$, is defined as

$$|C|_{\mathcal{K}}^{\mathbf{I}} = \sum_{a \in \mathbf{I}} bed(\mathcal{K}, a:C) . \quad (2)$$

122 The *crisp cardinality* (denoted $\lceil C \rceil_{\mathcal{K}}^{\mathbf{I}}$) is defined similarly by replacing in
 123 Eq. 2 the term $bed(\mathcal{K}, a:C)$ with $\lceil bed(\mathcal{K}, a:C) \rceil$.

124 Eventually, we say that the *application* of rule $C \sqsubseteq A$ to individual a
 125 w.r.t. $\mathcal{K}$ is $bed(\mathcal{K}, C:a)$ and that rule $C \sqsubseteq A$ *applies* to individual a w.r.t. $\mathcal{K}$
 126 if $bed(\mathcal{K}, C:a) > 0$.

127 3. PN-OWL

128 We are going now to present PN-OWL. At first, we formally present the
 129 learning problem we will address, then present our algorithm conceptually
 130 and eventually formalize PN-OWL.

131 3.1. The Learning Problem

132 We illustrate the learning problem using an example (see also [14, 19, 20] for
 133 analogous examples).

134 **Example 3.1.** *For the sake of illustrative purposes, let us consider a struc-*
 135 *tural simple OWL 2 ontology that describes the meaningful entities of mam-*
 136 *mography screening data. The target is the prediction of breast cancer [21].*
 137 *An excerpt of this ontology is given in Fig. 2, while an excerpt of the patient*
 138 *data is given in Table 1. Patients who have breast cancer are called positive*
 139 *examples, while those who do not are called negative examples.*




Fig. 2. Excerpt of the mammography ontology.

Table 1

Excerpt of the mammographic patient data: ‘-’ indicates that the value of the ‘attribute’ is unknown.

Patient	hasDensity	hasShape	hasMargin	hasBiRads	hasAge	...
p0	low	lobular	spiculated	5	67	...
p10	high	irregular	spiculated	5	76	...
p102	-	irregular	ill-defined	4	58	...
p108	low	round	circumscribed	4	57	...
p109	-	irregular	ill-defined	5	33	...
p110	low	irregular	ill-defined	4	45	...
p111	low	irregular	ill-defined	5	71	...
...	...	...	...	...	...	...

140 The set $I_{\mathcal{E}^+}$ of positive and the set $I_{\mathcal{E}^-}$ of negative examples/individuals
 141 contain

$$\{p0, p10, p109, p111\} \subseteq I_{\mathcal{E}^+} \quad (3)$$

$$\{p102, p108, p110\} \subseteq I_{\mathcal{E}^-} . \quad (4)$$

142 Now, our goal is to determine what characterizes the patients with cancer (our
 143 target class T). That is, we would like to induce OWL 2 class expressions
 144 whose instances include as many positive examples as possible and as few

145 *negative examples as possible.*

146 *Now, assuming that all positive individuals are instances of the class*
 147 **ToLearn**, *while all others are instances of the class* **NotToLearn** *(see Fig. 2),*
 148 *then one may learn from the ontology the following fuzzy concept/class in-*
 149 *clusion rule, expressed in fuzzyDL syntax [22]:*

150 151 152 153	<pre> (implies (and (some hasMargin ill-defined) (some hasShape irregular) (some hasAge hasAge_high)) ToLearn 0.853) </pre>	<div style="border-left: 1px solid black; padding-left: 10px;"> <i>if the margin is ill-defined, the shape is irregular, and the age is high then it is breast cancer with confidence 0.853</i> </div>
--------------------------	---	--

151 *where hasAge_high is the fuzzy set (see Fig. 3)*

152 `(define-fuzzy-concept hasAge_high right-shoulder (0,150,54,67)) .`
 153

154 *For instance, as we will see later on, by referring to the patient data in*
 155 *Table 1, by this rule patient p111 will correctly be classified, while patient*
 156 *p102 will incorrectly be classified as having breast cancer. The confidence*
 157 *value of 0.853 expresses the percentage of instances correctly classified among*
 158 *all those that satisfy the antecedent of this rule. This metric is also referred*
 159 *to as the precision of the rule.*

160 *The left-hand expression in the learnt rule is expressed in DL syntax as*
 161 *the concept*

$$\begin{aligned}
 &\exists \text{hasMargin.ill-defined} \sqcap \\
 &\exists \text{hasShape.irregular} \sqcap \\
 &\exists \text{hasAge.hasAge_high}
 \end{aligned}
 \tag{5}$$



Fig. 3. Fuzzy set hasAge_high.

162 and the learnt rule can be expressed as

$$\begin{aligned} & \langle \exists \text{hasMargin.ill-defined} \sqcap \\ & \exists \text{hasShape.irregular} \sqcap \\ & \exists \text{hasAge.hasAge_high} \sqsubseteq \text{ToLearn}, 0.853 \rangle \end{aligned} \quad (6)$$

163 The TBox of the mammography KB contains GCIIs such as

$$\begin{aligned} \text{Measure} & \sqsubseteq \text{Margin} \\ \text{Margin} & \sqsubseteq \text{ill-defined} \\ \text{Margin} & \sqsubseteq \text{spiculated} \end{aligned}$$

164 The patient p102 can be encoded as the concept assertion

$$\begin{aligned} \text{p102} : \text{Patient} \sqcap \exists \text{hasShape.irregular} \sqcap \\ \exists \text{hasMargin.ill-defined} \sqcap \\ \exists \text{hasAge.} =_{58} \sqcap \exists \text{hasBiRads.} =_4 . \end{aligned} \quad (7)$$

165 Furthermore, let BC be the concept in Eq. 5 and $\mathcal{K}$ be the mammography KB,
166 then it can be shown that

$$\text{bed}(\mathcal{K}, \text{p102} : \exists \text{hasAge.hasAge_high}) = 0.308$$

167 as $\text{hasAge_high}(58) = 0.308$ and, thus,

$$\text{bed}(\mathcal{K}, \text{p102} : \text{BC}) = 0.308 .$$

168 Moreover, if we add the learnt rule $\langle \text{BC} \sqsubseteq \text{ToLearn}, 0.853 \rangle$ to $\mathcal{K}$, i.e. the rule
169 in Eq. 6, then we will infer that

$$\text{bed}(\mathcal{K} \cup \{ \langle \text{BC} \sqsubseteq \text{ToLearn}, 0.853 \rangle \}, \text{p102} : \text{ToLearn}) = 0.308 \cdot 0.853 = 0.262 .$$

170 That is, we classify patient p102 as having breast cancer to degree 0.262.

171 Similarly, one may verify that

$$\begin{aligned} \text{bed}(\mathcal{K} \cup \{ \langle \text{BC} \sqsubseteq \text{ToLearn}, 0.853 \rangle \}, \text{p109} : \text{ToLearn}) & = 0.0 \\ \text{bed}(\mathcal{K} \cup \{ \langle \text{BC} \sqsubseteq \text{ToLearn}, 0.853 \rangle \}, \text{p110} : \text{ToLearn}) & = 0.0 \\ \text{bed}(\mathcal{K} \cup \{ \langle \text{BC} \sqsubseteq \text{ToLearn}, 0.853 \rangle \}, \text{p111} : \text{ToLearn}) & = 0.853 . \end{aligned}$$

172 It can easily also be verified that

$$\begin{aligned} |\text{BC}|_{\mathcal{K}}^{\text{I}} & \geq 0.262 + 0.0 + 0.0 + 0.853 = 1.115 \\ |\text{BC} \sqcap \text{ToLearn}|_{\mathcal{K}}^{\text{I}} & \geq 0.853 \end{aligned}$$

173 and that $|\text{BC} \sqcap \text{ToLearn}|_{\mathcal{K}}^{\mathbf{l}_{\mathcal{K}}} \leq |\text{BC}|_{\mathcal{K}}^{\mathbf{l}_{\mathcal{K}}}$.

174 Eventually, the quantity

$$\frac{|\text{BC} \sqcap \text{ToLearn}|_{\mathcal{K}}^{\mathbf{l}_{\mathcal{K}}}}{|\text{BC}|_{\mathcal{K}}^{\mathbf{l}_{\mathcal{K}}}} = 0.853$$

175 is the confidence/precision of the rule $\text{BC} \sqsubseteq \text{ToLearn}$.

176

□

177 Our learning problem is formalised as follows. Considering

- 178 1. a satisfiable crisp KB $\mathcal{K}$ and its individuals $\mathbf{l}_{\mathcal{K}}$;
- 179 2. a *target concept name* T ;
- 180 3. a *classification function* $f_T: \mathbf{l}_{\mathcal{K}} \rightarrow \{-1, 0, 1\}$, where for each $a \in \mathbf{l}_{\mathcal{K}}$, the
- 181 values (*labels*) correspond to

$$f_T(a) = \begin{cases} -1 & a \text{ is a } \textit{negative} \text{ example } T \\ 0 & a \text{ is an } \textit{unlabelled} \text{ example } T \\ 1 & a \text{ is a } \textit{positive} \text{ example } T ; \end{cases}$$

- 182 4. the partitioning of the examples into

$$\begin{aligned} \mathcal{E}^- &= \{(a, -1) \mid a \in \mathbf{l}_{\mathcal{K}}, f_T(a) = -1\} \\ \mathcal{E}^u &= \{(a, 0) \mid a \in \mathbf{l}_{\mathcal{K}}, f_T(a) = 0\} \\ \mathcal{E}^+ &= \{(a, 1) \mid a \in \mathbf{l}_{\mathcal{K}}, f_T(a) = 1\} \end{aligned}$$

183 where $\mathcal{E}^+ \neq \emptyset$ is assumed. We define $\mathcal{E} = \mathcal{E}^+ \cup \mathcal{E}^- \cup \mathcal{E}^u$ as the set of all

184 examples, and with $\mathcal{E}' = \mathcal{E} \setminus \mathcal{E}^+$ the set of *non-positive* examples;

- 185 5. the set of individuals $\mathbf{l}_{\mathcal{S}} = \{a \mid (a, l) \in \mathcal{S}\}$, where $\mathcal{S} \subseteq \mathcal{E}$ is a set of
- 186 examples. Moreover, we define

$$\begin{aligned} \mathbf{l}_{\mathcal{E}^-} &= \{a \mid (a, -1) \in \mathcal{E}^-\} \triangleright \text{the negative individuals} \\ \mathbf{l}_{\mathcal{E}^u} &= \{a \mid (a, 0) \in \mathcal{E}^u\} \triangleright \text{the unlabelled individuals} \\ \mathbf{l}_{\mathcal{E}^+} &= \{a \mid (a, 1) \in \mathcal{E}^+\} \triangleright \text{the positive individuals} \\ \mathbf{l}_{\mathcal{E}'} &= \mathbf{l}_{\mathcal{K}} \setminus \mathbf{l}_{\mathcal{E}^+} \triangleright \text{the non-positive individuals} . \end{aligned}$$

187 For each positive individual $a \in \mathbf{l}_{\mathcal{E}^+}$ there is an assertion $a:T$ in $\mathcal{K}$,

188 while for each negative individual $a \in \mathbf{l}_{\mathcal{E}^-}$ there is an assertion $a:\text{Not}T$

189 in $\mathcal{K}$, where $\text{Not}T$ is a concept name not occurring anywhere else in $\mathcal{K}$;

- 190 6. a *hypothesis space* of classifiers $\mathcal{H} = \{h: \mathbf{l}_{\mathcal{K}} \rightarrow [0, 1]\}$;
- 191 7. a *training set* $\mathcal{E}_{train} \subset \mathcal{E}$ of individual-label pairs, with $\mathcal{E}_{train} \cap \mathcal{E}^+ \neq \emptyset$;
- 192 8. a *test set* $\mathcal{E}_{test} = \mathcal{E} \setminus \mathcal{E}_{train}$, with $\mathcal{E}_{test} \cap \mathcal{E}^+ \neq \emptyset$.

193 **Example 3.2.** Consider Example 3.1. It can be verified that the mammogra-
 194 phy KB is satisfiable. The target class T is the class **ToLearn** whose instances
 195 are the patients having breast cancer, i.e. the set of positive individuals $\mathbf{l}_{\mathcal{E}^+}$
 196 are instances of **ToLearn** and contains $\{\mathbf{p0}, \mathbf{p10}, \mathbf{p109}, \mathbf{p111}\}$, while the set of
 197 negative individuals is $\mathbf{l}_{\mathcal{E}^-} = \mathbf{l}_{\mathcal{K}} \setminus \mathbf{l}_{\mathcal{E}^+}$, i.e. the non-positive individuals, and con-
 198 tains $\{\mathbf{p102}, \mathbf{p108}, \mathbf{p110}\}$, which are also instances of the class **NotToLearn**.
 199 □

200 We write

$$\begin{aligned} \mathcal{E}(a) &= 1 & \text{if } a \in \mathbf{l}_{\mathcal{E}^+} \\ \mathcal{E}(a) &= 0 & \text{if } a \in \mathbf{l}_{\mathcal{E}^u} \\ \mathcal{E}(a) &= -1 & \text{if } a \in \mathbf{l}_{\mathcal{E}^-} . \end{aligned}$$

201 The general goal is to learn a classifier function $\bar{h} \in \mathcal{H}$ that is the result of
 202 *Empirical Risk Minimisation* (ERM) on $\mathcal{E}_{train}$ [14]:

$$\begin{aligned} \bar{h} &= \arg \min_{h \in \mathcal{H}} R(h, \mathcal{E}_{train}) \\ &= \frac{1}{|\mathcal{E}_{train}|} \sum_{a \in \mathbf{l}_{\mathcal{E}_{train}}} L(h(a), \mathcal{E}_{train}(a)) , \end{aligned} \tag{8}$$

203 where L is a *loss function* that measures how different the prediction of a
 204 hypothesis is from the true label and $R(h, \mathcal{E}_{train})$ is the *risk* associated with
 205 hypothesis h over $\mathcal{E}_{train}$, defined as the expectation of the loss function over
 206 the training set $\mathcal{E}_{train}$. The effectiveness of the learnt classifier $\bar{h}$ is then
 207 assessed by $R(\bar{h}, \mathcal{E}_{test})$ on the test set $\mathcal{E}_{test}$ [14].

208 In our learning setting, a hypothesis $h \in \mathcal{H}$ is a set of fuzzy GCIs/rules

209 of the form

$$\langle C_1 \sqsubseteq P_1, \alpha_1 \rangle, \dots, \langle C_h \sqsubseteq P_h, \alpha_h \rangle \quad (9)$$

$$@^+(P_1, \dots, P_h) \sqsubseteq P \quad (10)$$

$$\langle D_1 \sqsubseteq N_1, \beta_1 \rangle, \dots, \langle D_k \sqsubseteq N_k, \beta_k \rangle \quad (11)$$

$$@^-(N_1, \dots, N_k) \sqsubseteq N \quad (12)$$

$$@ (P, N) \sqsubseteq T, \quad (13)$$

210 where each P_i, P, N_j, N are new class names not occurring in $\mathcal{K}$, and α_i, β_j
 211 are the confidence degree of the relative GCIs, $@^+, @^-, @$ are aggregation
 212 operators, and each C_i, D_j is a fuzzy $\mathcal{EL}(\mathbf{D})$ concept expression [23] defined
 213 as (v is a boolean value)

$$\begin{aligned} C &\longrightarrow \top \mid A \mid \exists r.C \mid \exists s.\mathbf{d} \mid C_1 \sqcap C_2 \\ \mathbf{d} &\longrightarrow ls(a, b) \mid rs(a, b) \mid tri(a, b, c) \mid trz(a, b, c, d) \mid =_v. \end{aligned}$$

214 Informally, (i) each P_i ‘rule’ will tell us why an individual should be positive;
 215 (ii) then we aggregate the various degrees of positiveness via the aggregator
 216 operator $@^+$; (iii) on the other hand, each N_i ‘rule’ will tell us why an
 217 individual should be *not* positive; (iv) then we aggregate the various degrees
 218 of non-positiveness via the aggregator operator $@^-$. Typically, both $@^+$
 219 and $@^-$ are the max operator; finally, (v) we use the last ‘rule’ to establish
 220 whether or not an individual is an instance of T (*viz.* is positive or not
 221 positive) by combining the degree of being positive or not via the $@$ operator.
 222 A simple choice for $@$ is the following and is the one we will adopt:

223 $(\star)$ if the degree p of being positive is greater than the degree n of
 224 being non-positive then p , else 0.

225 Now, for $a \in \mathbf{I}_{\mathcal{K}}$, the *classification prediction value* $h(a)$ of a , T and $\mathcal{K}$ is
 226 defined as

$$h(a) = bed(\mathcal{K} \cup h, a:T). \quad (14)$$

227 **Remark 1.** Note that, as stated above, essentially a hypothesis is a sufficient
 228 condition for being an individual instance of a target concept to some degree.
 229 If $h(a) = 0$ then we say that a is not a positive instance of T , while if $h(a) > 0$

230 then a is a positive instance of T to degree $h(a)$. As a consequence, we will
 231 distinguish between positive and non-positive examples of T only. That is,
 232 negative examples and unlabelled examples are indistinguishable. $\square$

233 **Example 3.3.** Consider Example 3.2. As we have seen, a P -rule example
 234 following Eq. 9 is rule p_1 defined as

$$\langle \exists \text{hasMargin.ill-defined} \sqcap \exists \text{hasShape.irregular} \sqcap \exists \text{hasAge.hasAge_high} \sqsubseteq P_1, 0.853 \rangle \quad (15)$$

235 while an example of N -rule following Eq. 11 is rule n_1 defined as

$$\langle \exists \text{hasDensity.low} \sqcap \exists \text{hasAge.hasAge_medium} \sqcap \exists \text{hasBiRads.hasBiRads_medium} \sqsubseteq N_1, 1.0 \rangle, \quad (16)$$

236 where hasAge_medium is defined as $\text{tri}(40, 54, 67)$ and hasBiRads_medium is
 237 defined as $\text{tri}(3, 4, 5)$. Now, by adding rules p_1, n_1 to the KB one may verify
 238 that

$$\begin{aligned} \text{bed}(\mathcal{K} \cup \{p_1, n_1\}, \text{p102:P}_1) &= 0.262 \\ \text{bed}(\mathcal{K} \cup \{p_1, n_1\}, \text{p102:N}_1) &= 0.692 \\ \text{bed}(\mathcal{K} \cup \{p_1, n_1\}, \text{p111:P}_1) &= 0.853 \\ \text{bed}(\mathcal{K} \cup \{p_1, n_1\}, \text{p111:N}_1) &= 0.0. \end{aligned}$$

239 Therefore, by applying $(\star)$ we would correctly classify patient p102 as not
 240 having breast cancer, while correctly p111 does so. $\square$

241 **Remark 2.** The set of hypotheses defined by this syntax is potentially infinite
 242 due to conjunction and the nesting of existential restrictions in the concept
 243 expressions. As we will see later on, we will impose further restrictions such
 244 as the maximum number of conjuncts and the maximum depth of existential
 245 nestings allowed. $\square$

246 We conclude by saying that a hypothesis h covers (resp. θ -covers, for $\theta \in$
 247 $(0, 1]$) an individual $a \in \mathcal{I}_{\mathcal{K}}$ iff $h(a) > 0$ (resp. $h(a) \geq \theta$), and indicate
 248 with $\text{Cov}(h)$ (resp. $\text{Cov}_{\theta}(h)$) the set of covered (resp. θ -covered) individuals.
 249 Moreover, for a rule $C \sqsubseteq T$, the *confidence degree* (also called the *precision*) of

250 $C \sqsubseteq T$ w.r.t. $\mathcal{K}$ and a set of positive individuals P , denoted $cf(C \sqsubseteq T, \mathcal{K}, P)$,
 251 is defined as

$$cf(C \sqsubseteq T, \mathcal{K}, P) = \frac{|C|_{\mathcal{K}}^P}{|C|_{\mathcal{K}}^I}, \quad (17)$$

252 which is the proportion of positive individuals covered by C w.r.t. the indi-
 253 viduals covered by C . Clearly, $cf(C \sqsubseteq T, \mathcal{K}, P) \in [0, 1]$ and the closer the
 254 confidence is to 1 the ‘more precise’ is $C \sqsubseteq T$, *i.e.* the less non-positive
 255 individuals are covered by it. In addition, the *support* of $C \sqsubseteq T$ w.r.t. $\mathcal{K}$ and
 256 a set of individuals I , denoted $supp(C \sqsubseteq T, \mathcal{K}, I)$, is defined as

$$supp(C \sqsubseteq T, \mathcal{K}, I) = \frac{|C|_{\mathcal{K}}^I}{|I|}. \quad (18)$$

257 3.2. The Learning Method

258 Before presenting our learning algorithm, we first conceptually illustrate its
 259 principle by relying on Fig. 4.

260 In the beginning, consider the sets of all individuals, the positive, the
 261 negative, and the unlabelled individuals, respectively the sets $I_{\mathcal{K}}$, $I_{\mathcal{E}^+}$, $I_{\mathcal{E}^-}$ and
 262 $I_{\mathcal{E}^u}$ (Fig. 4 (a)).

263 At the first stage, the P-stage, we consider the entire training set $\mathcal{E}_{train} =$
 264 $\mathcal{E}$ and try to maximize the covering of positive individuals while minimizing
 265 the covering of non-positive individuals. Specifically, let us assume that we
 266 have learnt a hypothesis h_P (a set of rules) with a covering $Cov_{\theta_P}(h_P)$, as
 267 depicted in Fig. 4 (b). Here, the value θ_P acts as a confidence threshold for the
 268 learnt rules in hypothesis h_P . Note that $Cov_{\theta_P}(h_P)$ has to contain positive
 269 individuals, *i.e.* $Cov_{\theta_P}(h_P) \cap I_{\mathcal{E}^+} \neq \emptyset$, but may also contain negative and
 270 unlabelled individuals. We call the individuals in $TP = Cov_{\theta_P}(h_P) \cap I_{\mathcal{E}^+}$ *true*
 271 *positives*, while call those in $FP = Cov_{\theta_P}(h_P) \setminus I_{\mathcal{E}^+}$ *false positives*, *i.e.* a false
 272 positive is an individual that is erroneously classified by h_P as an instance
 273 of the target class T , while in fact, it is not (it might be an unlabelled or
 274 a negative example). This phase ends with a set of rules of the form as in
 275 Eqs. 9-10. For instance, by referring to Example 3.3, one may learn at the
 276 P-stage the rule p_1 covering individuals p102 and p111. The latter is a true
 277 positive, while the former is a false positive.

278 In the next stage, the N-stage, to increase the effectiveness of the classi-
 279 fiers, we try to remove as many possible false positives in FP , while avoiding
 280 removing, if possible, any of the true positives in TP . To do so, we set up
 281 a new learning problem: the new target class is FP , where the negative




Fig. 4. How PN-OWL works: (a) Original training set; (b) Coverage $Cov_{\theta_P}(h_P)$ w.r.t. learnt hypothesis h_P after the P-stage; (c) Starting dataset for N-stage: the new target class is the false positives FP of the P-stage, while the negative individuals are the initial positives; (d) Coverage $Cov_{\theta_N}(h_N)$ w.r.t. learnt hypothesis h_N after the N-stage; (e) Final scenario.

individuals are those in TP and the positives are those in FP . Of course, the N-stage applies only if $FP \neq \emptyset$. The setup of the N-stage is depicted in Fig. 4 (c). Specifically, let us assume that we have learnt now a hypothesis h_N with a covering $Cov_{\theta_N}(h_N)$, as depicted in Fig. 4 (d). Note that we may have another parameter θ_N as a confidence threshold for the learnt rules in hypothesis h_N . This phase ends with a set of rules of the form as in Eqs. 11-12. So, in general, at the end of the two stages, the situation may be as depicted in Fig. 4 (e). For instance, continuing referring to Example 3.3, one may learn at the N-stage the rule n_1 covering individual p102 only.

Eventually, we aggregate the P-rules and N-rules via $(\star)$. This latter step ends with the rule of the form as in Eq. 13. Referring to Example 3.3, this would allow us to correctly remove patient p102 from those classified as

294 having breast cancer.

295 3.3. The Learning Algorithm PN-OWL

296 We now formalize PN-OWL, which we have conceptually illustrated in the
 297 section before. Essentially, at the P-stage (resp. N-stage) our algorithm in-
 298 vokes a learner, called *stage learner*, that generates a set h_P (resp. h_N) of
 299 fuzzy $\mathcal{EL}(\mathbf{D})$ candidate GCIs that has, respectively, the form

$$h_P = \{\langle C_1 \sqsubseteq T, \alpha_1 \rangle, \dots, \langle C_h \sqsubseteq T, \alpha_h \rangle\} \quad (19)$$

$$h_N = \{\langle D_1 \sqsubseteq FP, \beta_1 \rangle, \dots, \langle D_k \sqsubseteq FP, \beta_k \rangle\} \quad (20)$$

300 called *stage hypothesis*. In the following, we indicate with p_i the fuzzy GCI
 301 $\langle C_i \sqsubseteq T, \alpha_i \rangle$, while denote with n_j the fuzzy GCI $\langle D_j \sqsubseteq FP, \beta_j \rangle$. The rules
 302 in h_P (resp. h_N) will then be aggregated using the max aggregation operator.

303 The stage hypotheses are then combined into a final hypothesis for the
 304 target class T using aggregation operator $(\star)$.

305 As stage learner, we will use fuzzy FOIL- $\mathcal{DL}$ [14, 19, 24]. For completeness
 306 of the presentation, we will recap succinctly fuzzy FOIL- $\mathcal{DL}$ in the appendix.

307 The PN-OWL algorithm is shown in Algorithm 1. Note that the P-
 308 stage corresponds to steps 1-5, while the N-stage corresponds to steps 15-19
 309 in which at step 19 we invoke the stage learner trying to cover as many false
 310 positives as possible. The remaining steps deal with the construction of the
 311 final classifier ensemble as per Eqs. 9-13.

312 Eventually, for an individual $a \in \mathbf{I}_{\mathcal{K}}$, the *classification prediction value*
 313 of PN-OWL for individual a is $h(a)$, where h is the hypothesis returned
 314 by PN-OWL. Moreover, we say that PN-OWL *classifies* a as instance of
 315 target class T if $h(a) > 0$.

316 4. Evaluation

317 We have implemented the algorithm within the *FuzzyDL-Learner* system [25].

318 *Datasets.* Several OWL 2 ontologies from different domains have been se-
 319 lected as illustrated in Table 2, which reports the DL the ontology refers to,
 320 the number of concept/class names, object properties, datatype properties,
 321 and individuals in the ontology. For each ontology $\mathcal{K}$ we indicate also the
 322 number $|\mathcal{E}^+|$ of positive examples. All other individuals are non-positive and
 323 we set $\mathcal{E}^- = \mathcal{E}' = \mathbf{I}_{\mathcal{K}} \setminus \mathbf{I}_{\mathcal{E}^+}$.

Algorithm 1 PN-OWL

Input: KB $\mathcal{K}$, training set $\mathcal{E}$, target concept name T , set of parameters (see Table 3)
Output: Hypothesis h as by Eq. 9-13.

```

1: // P-stage
2:  $Pos \leftarrow I_{\mathcal{E}^+}$ ;
3:  $Neg \leftarrow I_{\mathcal{E}^-}$ ;
4:  $U \leftarrow I_{\mathcal{K}} \setminus (Pos \cup Neg)$ ;
5:  $h_P \leftarrow \text{FUZZYSTAGELARNER}(\mathcal{K}, T, Pos, Neg, U, \theta_P, \eta_P)$ ;  $\triangleright$  P-Stage hypothesis  $h_P$ , i.e. set of
   axioms of the form  $\langle C_i \sqsubseteq T, \alpha_i \rangle$ 
6: if  $h_P = \emptyset$  then return  $\emptyset$ ;  $\triangleright$  Nothing learnt, exit
7:  $Cov \leftarrow Cov_{\theta_P}(h_P)$ ;  $\triangleright$  P-stage Coverage
8:  $TP \leftarrow Cov_{\theta_P}(h_P) \cap I_{\mathcal{E}^+}$ ;  $\triangleright$  True positives
9:  $FP \leftarrow Cov_{\theta_P}(h_P) \setminus I_{\mathcal{E}^+}$ ;  $\triangleright$  False positives
10: // Start building classifier  $h$ 
11:  $h \leftarrow \{ \langle C_i \sqsubseteq P_i, \alpha_i \rangle, \mid \langle C_i \sqsubseteq T, \alpha_i \rangle \in h_P, P_i \text{ new } \}$ ;  $\triangleright$  As per Eq. 9
12: if  $FP = \emptyset$  then  $\triangleright$  No N-stage, exit with aggregated  $h_P$ 
13:    $h \leftarrow h \cup \{ @^+(P_1, \dots, P_h) \sqsubseteq T \}$ ;  $\triangleright$  No need of new  $P$  in Eq. 10
14:   return  $h$ ;
15: // N-stage
16:  $Pos \leftarrow FP$ ;
17:  $Neg \leftarrow I_{\mathcal{E}^+}$ ;
18:  $U \leftarrow I_{\mathcal{K}} \setminus (Pos \cup Neg)$ ;
19:  $h_N \leftarrow \text{FUZZYSTAGELARNER}(\mathcal{K}, FP, Pos, Neg, U, \theta_N, \eta_N)$ ;  $\triangleright$  N-Stage hypothesis  $h_N$ , i.e. set of
   axioms of the form  $\langle D_j \sqsubseteq FP, \beta_j \rangle$ 
20: // Build final classifier ensemble  $h$ 
21: if  $h_N = \emptyset$  then  $\triangleright$  No learning in N-stage, return aggregated  $h_P$ 
22:    $h \leftarrow h \cup \{ @^+(P_1, \dots, P_h) \sqsubseteq T \}$ ;  $\triangleright$  No need of new  $P$  in Eq. 10
23:   return  $h$ ;
24:  $h \leftarrow h \cup \{ @^+(P_1, \dots, P_h) \sqsubseteq P \mid P \text{ new } \}$ ;  $\triangleright$  As per Eq. 10
25:  $h \leftarrow h \cup \{ \langle D_j \sqsubseteq N_j, \beta_j \rangle, \mid \langle D_j \sqsubseteq FP, \beta_j \rangle \in h_N, N_j \text{ new } \}$ ;  $\triangleright$  As per Eq. 11
26:  $h \leftarrow h \cup \{ @^-(N_1, \dots, N_k) \sqsubseteq N \mid N \text{ new } \}$ ;  $\triangleright$  As per Eq. 12
27:  $h \leftarrow h \cup \{ @^-(P, N) \sqsubseteq T \}$ ;  $\triangleright$  As per Eq. 13
28: return  $h$ ;

```

324 The ontologies **Iris**, **Wine**, **Wine Quality** and **Yeast** are built from the
 325 well-known *UC Irvine Machine Learning Repository* (UCIMLR) [26] and
 326 have been transformed from the CSV format, provided by that repository,
 327 into OWL 2 ontologies according to the procedure described in [14].

328 All other ontologies, except **malware**, belong to the well-known SML-
 329 Bench dataset [21]. The **malware** ontology has been described in [27].

330 **Remark 3.** *Note that all but Lymphography have datatype properties. While*
 331 *evaluating ontology-based learning algorithms is untypical on numerical datatype*
 332 *properties, we believe it is interesting to do so as an important ingredient of*
 333 *our algorithm is the use of fuzzy concrete datatype properties to improve the*
 334 *human understandability, i.e. the explainability of the classification decision*

Table 2
Facts about the ontologies of the evaluation.

ontology	DL	class.	obj. prop.	data prop	ind.	target T	pos
NTN	$SHOIN(\mathcal{D})$	51	29	9	723	ToLearn.Woman	46
Lymphography	$\mathcal{ALC}$	50	0	0	148	ToLearn	81
Mammographic	$\mathcal{ALC}(\mathcal{D})$	20	3	2	975	ToLearn	445
Malware	$\mathcal{ALH}(\mathcal{D})$	192	6	10	5669	malware	500
Iris	$\mathcal{AL\mathcal{E}HF}(\mathcal{D})$	4	0	5	150	Iris-versicolor	50
						Iris-virginica	50
Wine	$\mathcal{AL\mathcal{E}HF}(\mathcal{D})$	3	0	13	178	1	59
						2	71
						3	48
Wine Quality	$\mathcal{AL\mathcal{E}HF}(\mathcal{D})$	7	0	11	6497	GoodRedWine	217
Yeast	$\mathcal{AL\mathcal{E}HF}(\mathcal{D})$	11	0	8	1462	CYT	444

process.

Measures. We considered the following well-known effectiveness measures (see also [14]), which we recap here for the sake of completeness. Specifically, consider a learnt classifier h and let us assume to have added it to the KB $\mathcal{K}$. In our setting, we always have the condition that if the classifier prediction value $h(a)$ of an individual a is non-zero then the learner classifies a as an instance of T , *i.e.* h predicts a to be a positive example if $h(a) > 0$. As all individuals are either positive or non-positive, we will consider the following measures, all of which are based on crisp cardinality.

The *True Positives*, denoted TP , is defined as the number of instances of T that are positive, *i.e.* $TP = |T|_{\mathcal{K}}^{\mathcal{E}+}$. The *False Positives*, denoted FP , is defined as the number of instances of T that are not positive, *i.e.* $FP = |T|_{\mathcal{K}}^{\mathcal{E}'}$. *Precision*, or *Confidence*, denoted P , is defined as the fraction of true positives w.r.t. the covered examples of h , *i.e.* $P = \frac{TP}{|T|_{\mathcal{K}}^{\mathcal{E}}}$. *Recall*, denoted R , is defined as fraction of true positives w.r.t. all positives, *i.e.* $R = \frac{TP}{|I_{\mathcal{E}+}|}$ and *F1-score*, denoted $F1$, is defined as $F1 = 2 \cdot \frac{P \cdot R}{P + R}$.

Parameters. Some of the salient parameters used within our algorithm are reported in Table 3 of which the maximal role depth (usually, $d_P = d_N$) is determined manually a priori by inspecting the ontology. For the other

Table 3
Some salient parameters of the PN-OWL algorithm.

param	description
θ_P	confidence threshold for positive rules of P-stage
θ_N	confidence threshold for negative rules of N-stage
η_P	non-positive coverage percentage threshold for positive rules of P-stage
η_N	non-positive coverage percentage threshold for negative rules of N-stage
c_P	maximal number of conjuncts for positive rules of P-stage
c_N	maximal number of conjuncts for negative rules of P-stage
d_P	maximal role depth for positive rules of P-stage
d_N	maximal role depth for negative rules of P-stage

parameters, we generated automatically via random grid search various parameter configurations $\langle \theta_P, \theta_N, \eta_P, \eta_N, c_P, c_N, d_P, d_N \rangle$ by varying confidence thresholds, non-positive coverage percentage, and maximal number of conjuncts.

For each parameter configuration, a stratified k -fold cross-validation design (i.e. each fold contains the same proportions of positive and non-positive instances of T) was adopted (specifically, $k = 5$) to determine the macro average of the above-described effectiveness measures.

In all tests, we have that $l_{\mathcal{E}} = l_{\mathcal{K}}$ and that there is at least one positive example in each fold. For each fold, during the training phase, we remove all assertions involving test examples from the ontology, and, thus, restrict the training phase to training examples only. All experimental data is available from the downloadable resource ¹. The resource contains the executable code, the ontologies, and each ontology, the parameter configuration that produced the best test macro average F1-score together with learnt rules and effectiveness measures for each fold.

It is worth noting that a typical parameter configuration is as follows, but may vary depending on the ontology.

P-stage. $c_P = 5, d_P = 1, \theta_P = 0.1, \eta_P = 1.0$

N-stage. $c_N = 10, d_N = 1, \theta_N = 0.3, \eta_N = 0.2$.

¹<http://www.umbertostraccia.it/cs/software/FuzzyDL-Learner/download/pnowl.experiments.zip>

Let us briefly comment on it. During the P-stage, we would like to increase recall, that is the percentage of covered positives w.r.t. all positives, and then use the N-stage to remove the false positive. In this way, we ultimately increase recall and precision and, thus, the F1-score. So, we choose a low positive rule confidence threshold θ_P and high non-positive coverage percentage threshold η_P . In the N-stage however, we want to be more precise in removing the false positives to avoid removing true positives of the P-Stage. Therefore, we increase the confidence threshold θ_N , lower the non-positive coverage percentage threshold η_N , and increase the number of maximal conjuncts c_N .

We recall that for $@^+$, $@^-$ (resp. $@$) we used $\max$ (resp. $(\star)$). Also, for concept conjunction $\sqcap$ we used the t-norm $\min$. These could well be another set of parameters: however, the parameter space is already quite large, so we fixed these logical operators as specified. We will investigate the impact of other choices for these parameters in future work.

Concerning some other parameter settings, we also varied the number of fuzzy sets (3, 5, or 7). For c-means, we fixed the hyper-parameter to the default $m = 2$, the threshold to $\epsilon = 0.05$, and the number of maximum iterations to 100 from the experience we gained in previous experiments [14, 19] and taking into account that clustering is done for each single data property.

Remark 4. *We leave it for future work to look at e.g. methods to learn from the training data a threshold $0 \leq \tau_p \leq 1$ such that h predicts individual a to be a positive example if $h(a) > \tau_p$. In this paper, we will always have $\tau_p = 0$. More generally, if we would like to distinguish the negative examples from the unlabelled ones, we may try to learn a classifier h^- for negative examples and then define a decision method that predicts an individual a to be a positive (resp. negative) example based on the prediction value $h(a)$ (resp. $h^-(a)$) of a being a positive (resp. negative) example. That is, depending on the pair $\langle h(a), h^-(a) \rangle$, one may then define a decision criteria whether a is a positive or negative example, or just leave the prediction as unknown if there is not enough evidence of being one of the two.* $\square$

As baseline, we consider the learner Fuzzy FOIL- $\mathcal{DL}$ [19, 24], with best parameter setup as specified in [14]. Essentially, Fuzzy FOIL- $\mathcal{DL}$, is as PN-OWL, except that it stops after the P-stage and, thus, is as PN-OWL in which the negative set of rules h_N is by definition empty (*cf.* lines 21-23 of PN-OWL algorithm). This allows us to appreciate the added value (if any) in terms of the effectiveness of the N-stage phase.

Table 4

Results table. The measures are the macro average over the 5 folds w.r.t. the test set.

Dataset	Algorithm	Precision	Recall	F1	% Improvement
NTN	Fuzzy DL-FOIL	0.661	0.513	0.548	80.47%
	PN-OWL	1.000	0.980	0.989	
Lymphography	Fuzzy DL-FOIL	0.810	0.803	0.805	3.48%
	PN-OWL	0.836	0.841	0.833	
Mammographic	Fuzzy DL-FOIL	0.737	0.692	0.710	11.27%
	PN-OWL	0.746	0.831	0.790	
Malware	Fuzzy DL-FOIL	0.623	0.830	0.704	5.06%
	PN-OWL	0.701	0.818	0.740	
Iris	Fuzzy DL-FOIL	0.886	0.910	0.890	4.16%
	PN-OWL	0.949	0.910	0.927	
Wine	Fuzzy DL-FOIL	0.884	0.971	0.895	0.98%
	PN-OWL	0.933	0.904	0.914	
Wine Quality	Fuzzy DL-FOIL	0.227	0.917	0.363	27.93%
	PN-OWL	0.365	0.659	0.464	
YEAST	Fuzzy DL-FOIL	0.427	0.746	0.540	4.37%
	PN-OWL	0.432	0.815	0.564	

410 The results are reported in Table 4. For the UCIMLR datasets, in the
 411 case of multiple targets, the average of the measures has been considered.

412 *Discussion.* In Table 4, the last column reports the improvement of PN-
 413 OWL relative to the measure $F1$ over our baseline Fuzzy FOIL- $\mathcal{DL}$. Overall,
 414 despite the algorithm is conceptually simple, PN-OWL outperforms Fuzzy
 415 FOIL- $\mathcal{DL}$ and in some cases, the improvement is particularly high, such as
 416 for NTN, Mammographic and Wine Quality.

417 Essentially, for PN-OWL we were able to find a better compromise be-
 418 tween precision and recall than for FOIL- $\mathcal{DL}$. In particular, we were able
 419 to increase precision via the N-stage, after increasing recall via the P-stage
 420 confirming our conjecture that indeed the N-stage can remove the false pos-
 421 itives.

422 The overall lesson learnt with PN-OWL is that indeed the N-stage may
 423 provide a non-negligible contribution to improve the effectiveness of the clas-
 424 sification process provided one may find the appropriate balance between
 425 precision and recall. Unfortunately, searching the parameter space of PN-
 426 OWL for an optimum is quite time-consuming and a brute-force approach
 427 may likely not be feasible (at least not with our computational resources at

hand) thus, we used a random grid search. On the other hand, optimizing FOIL- $\mathcal{DL}$ is much easier as it has half of the parameters of PN-OWL.

5. Related Work

The problem of learning GCIs, addressed in works such as [8, 28, 29, 30, 31, 32, 33], is typically inspired by statistical relational learning, where classification rules are (possibly weighted) Horn clause theories [6]. The goal is to learn a concept description of the underlying DL language covering (possibly) all positive examples and (possibly) not covering any of the provided negative examples. The fuzzy case (see [19, 20, 24]) is a natural extension in which one relies on fuzzy DLs [3, 4] and fuzzy ILP (see *e.g.* [34]): while, in the former works the authors propose *fuzzy* FOIL-like algorithms that are inspired by fuzzy ILP variants such as [35, 36, 37], in other works such as *e.g.* [38, 39] they adapt the well-known FOIL-algorithm to the DLs case. As already mentioned, our two-stage algorithm follows conceptually PN-rule [9, 10], and consists of a P-stage trying to cover as many as possible instances of a target class and an N-stage trying to remove most of the non-positive examples covered by the P-stage. It is worth noting that what differentiates this method from all others is (typically) its second stage. Moreover, the main differences of PN-OWL w.r.t. PN-rule are:

- PN-rule operates with *tabular data* only, *i.e.* the data consists of attribute-value pairs (A, v) , while we are in the context of OWL 2 ontologies²;
- PN-rules are of the form $cond \rightarrow T$, where the condition *cond* is of the form $(A \in [l, h])$ or $(A \notin [l, h])$ for continuous attribute A ,³ while we have the conjunction of conditions in the rule body and each condition may be fuzzy, each rule is graded, and each conjunction may be either a class name or a restriction on attributes, where attributes may be also nested;
- PN-rule considers a completely different rule scoring and combination strategy than we use in PN-OWL. The latter can be represented in Fuzzy OWL 2 [5], while for the former we conjecture it cannot: so, we

²Tabular data can easily be mapped into OWL 2 ontologies as illustrated in; [14].

³If A is categorical then obviously *cond* is either of the forms $A = v$ or $A \neq v$.

459 left this option out as a fuzzy DL reasoner would not be able to reason
 460 with those types of rules.

461 Discrete boosting has been considered in [40], while [14] is a real-valued
 462 fuzzy variant of AdaBoost and differentiates from the previous one by using
 463 a descent-like gradient algorithm to search for the best alternative. Notably,
 464 this also deviates from ‘fuzzy’ rule learning AdaBoost variants, such as [41,
 465 42, 43, 44, 45].

466 The works [46, 47] consider *Kernel Methods* for inducing concept de-
 467 scriptions, [48, 49, 50] are inspired on *Decision Trees/Random Forests*, while
 468 [51, 52] consider essentially a *Naive Bayes* approach. Last but not least, [53]
 469 is inspired by *Genetic Programming* to induce concept expressions, while [54]
 470 is based on the *Reinforcement Learning* framework. Eventually, [55] proposes
 471 to use decision trees to learn so-called *disjointness axioms*, *i.e.* expressions
 472 of the form $C \sqcap D \sqsubseteq \perp$, declaring that class C and D are disjoint.

473 As pointed out in Remark 3, typically ontology-based learning algorithms
 474 as those listed above do not rely on numerical datatype properties (except [14,
 475 19, 20]), we believe it is interesting to do so, not only to increase possibly
 476 the effectiveness but also to improve the human understandability, *i.e.* the
 477 explainability of the classification decision process (*cf.* Example 3.3).

478 6. Conclusions & Future Work

479 We have presented a two-stage algorithm, called PN-OWL that is inspired
 480 on the PN-rule [9, 10] and adapted to the context of OWL. The main features
 481 of our algorithm are essentially the fact that (i) at the P-stage, it generates
 482 a set of fuzzy inclusion axioms, the P-rules, that cover as many as possible
 483 instances of the target class T without compromising too much the amount
 484 on non-positives; (ii) at the N-stage, it generates a set of fuzzy inclusion
 485 axioms, the N-rules, that cover as many as possible of non-positive instances
 486 of class T of the P-stage; (iii) the fuzzy inclusion axioms are then combined
 487 (aggregated) into a new fuzzy inclusion axiom describing sufficient conditions
 488 for being an individual classified as an instance of the target class T .

489 All generated fuzzy concept inclusion axioms can be encoded as *Fuzzy*
 490 *OWL 2* axioms, allowing a fuzzy DL reasoner to reason with them.

491 We have also conducted an extensive evaluation, comparing it with fuzzy
 492 FOIL- $\mathcal{DL}$. Our evaluation shows that, despite being our algorithm concep-
 493 tually simple, PN-OWL outperforms fuzzy FOIL- $\mathcal{DL}$ in terms of effective-

ness, though finding an optimal parameter configuration is much more time-consuming.

Concerning future work, besides investigating other learning methods, and future work mentioned in various places in the paper, we envisage various aspects worth to be investigated in more detail: *(i)* we would like to investigate the computational aspect: so far, for some ontologies, a learning run may take even a week (w.r.t. our available resources). Here, we would like to investigate both parallelization methods as well as investigate the impact, in terms of effectiveness, of efficient, logically sound, but not necessarily complete, reasoning algorithms; *(ii)* in principle, our two-stage algorithm PN-OWL is parametric w.r.t. the learner to be used during both the P-stage and the N-stage (*cf.* lines 5 and 19 of the PN-OWL algorithm): here we would like to investigate how to plug in another alternative such as FUZZY OWL-BOOST [14] and to verify its effectiveness; and *(iii)* we would like to assess also the impact of other alternative scoring functions to information gain (*cf.* Eq. A.1) within our setting, inclusive various choices of t-norms and aggregation functions.

Eventually, we would like to consider extending the hypothesis language $\mathcal{EL}(\mathbf{D})$ with so-called *threshold concepts* [56] of the form $C[\geq d]$ (resp. $C[\leq d]$), where $d \in [0, 1]$ and C is either a class name or an existential restriction, with the intended meaning “ $C[\geq d]$ (resp. $C[\leq d]$) is the fuzzy set of individuals that are instances of C to a degree greater (resp. smaller) than or equal to d ”. On our ongoing implementation, as an example of a rule, by referring to the Wine Quality ontology and target wine number 1, we generated an expression of the form

```
(implies (and (some alcohol alcohol_VH)[<= 0.786]
              (some sulfates sulfates_H)[>= 0.289]
              (some pH pH_L)[<= 0.106])
  1)
```

with intended meaning “*if, for an individual (wine) a , the alcohol level of being very high is smaller than or equal to 0.786, the sulfates level of being high is greater than or equal to 0.289 and the pH level of being low is smaller than or equal 0.106, then classify a to some extent (e.g. the minimum of the degrees of being a an instance of a conjunct) as an instance of the target class 1*”. This would provide a more fine-grained hypothesis language in which a threshold may be defined for each conjunct of a rule rather than via rule confidence.

Algorithm 2 Fuzzy FOIL- $\mathcal{DL}$

Input: KB $\mathcal{K}$, target concept name T , a set P (resp. N and U) of positive (resp. negative and unlabelled) examples, confidence threshold $\theta \in [0, 1]$, non-positive coverage percentage $\eta \in [0, 1]$

Output: A hypothesis, *i.e.* a set $h = \{\langle C_i \sqsubseteq T, \delta_i \rangle | 1 \leq i \leq k\}$ of fuzzy $\mathcal{EL}(\mathbf{D})$ GCIs

```

1:  $h \leftarrow \emptyset, Pos \leftarrow P, \phi \leftarrow \top \sqsubseteq T$ ;
2: while ( $Pos \neq \emptyset$ ) and ( $\phi \neq \text{null}$ ) do
   $\triangleright$  Loop until no improvement
3:    $\phi \leftarrow \text{LEARN-ONE-AXIOM}(\mathcal{K}, T, Pos, P, N, U, \theta, \eta)$ ;
   $\triangleright$  Learn one fuzzy  $\mathcal{EL}(\mathbf{D})$  GCI of the form  $C \sqsubseteq T$ 
4:   if  $\phi \in h$  then  $\triangleright$  axiom already learnt
5:      $\phi \leftarrow \text{null}$ ;
6:   if  $\phi \neq \text{null}$  then
7:      $\delta \leftarrow cf(\phi, \mathcal{K}, P)$ ;  $\triangleright$  Compute confidence of  $\phi$ 
8:      $h \leftarrow h \cup \{\langle \phi, \delta \rangle\}$ ;  $\triangleright$  Update hypothesis
9:      $Pos_\phi \leftarrow Pos \cap Cov(\langle \phi, \delta \rangle)$ ;
   $\triangleright$  Positives covered by  $\langle \phi, \delta \rangle$ 
10:     $Pos \leftarrow Pos \setminus Pos_\phi$ ;
   $\triangleright$  Update positives still to be covered
11: return  $h$ ;
```

531 Appendix A. The Stage Learner Fuzzy Foil- $\mathcal{DL}$

532 The procedure invocations FUZZYSTAGELARNER at steps 5 and 19 in
 533 the Algorithm 1 are calls to fuzzy FOIL- $\mathcal{DL}$ [14, 19, 24], which we briefly
 534 recap in this section. Essentially, fuzzy FOIL- $\mathcal{DL}$ carries on inducing GCIs
 535 until as many positive examples are covered or nothing new can be learnt, in
 536 general terms operates as follows:

- 537 1. start from concept $\top$;
- 538 2. apply a refinement operator to find more specific fuzzy $\mathcal{EL}(\mathbf{D})$ concept
 539 candidates;
- 540 3. score them to choose the best candidate;
- 541 4. re-apply the refinement operator until a good candidate is found;
- 542 5. iterate the whole procedure until a satisfactory coverage of the positive
 543 examples is achieved.

544 As shown on Algorithm 2, when a rule is induced (step 3), the positive
 545 examples still to be covered are updated (step 9 and 10). To induce an
 546 axiom (step 3), LEARN-ONE-AXIOM is invoked (see Algorithm 3),

547 *Refinement operator.* The refinement operator is the same as in [14, 20, 24,
 548 57]. It takes as input a concept C and generates a more specific concept

Table A.5
Downward Refinement Operator.

$$\rho(C) = \begin{cases} \mathbf{A}_{\mathcal{K}} \cup \{\exists r. \top \mid r \in \mathbf{R}_{\mathcal{K}}\} \cup \\ \{\exists s. d \mid s \in \mathbf{S}_{\mathcal{K}}, d \in \mathcal{D}\} \cup \\ \{\exists s. =_b, \mid s \in \mathbf{B}_{\mathcal{K}}, b \in \{\mathbf{t}, \mathbf{f}\}\} & \text{if } C = \top \\ \\ \{A' \mid A' \in \mathbf{A}_{\mathcal{K}}, \mathcal{K} \models A' \sqsubseteq A\} \cup \\ \{A \sqcap A'' \mid A'' \in \rho(\top)\} & \text{if } C = A \\ \\ \{\exists r. D' \mid D' \in \rho(D)\} \cup \\ \{(\exists r. D) \sqcap D'' \mid D'' \in \rho(\top)\} & \text{if } C = \exists r. D, r \in \mathbf{R}_{\mathcal{K}} \\ \\ \{(\exists s. d) \sqcap D \mid D \in \rho(\top)\} & \text{if } C = \exists s. d, s \in \mathbf{S}_{\mathcal{K}}, \\ & d \in \mathcal{D} \\ \\ \{(\exists s. =_b) \sqcap D \mid D \in \rho(\top)\} & \text{if } C = \exists s. =_b, s \in \mathbf{B}_{\mathcal{K}}, \\ & b \in \{\mathbf{t}, \mathbf{f}\} \\ \\ \{C_1 \sqcap \dots \sqcap C'_i \dots \sqcap C_n \mid C'_i \in \rho(C_i)\} & \text{if } C = C_1 \sqcap \dots \sqcap C_n \end{cases}$$

549 description candidates D ⁴ (see Table A.5).

550 *The GCI scoring function.* The scoring function used in fuzzy FOIL- $\mathcal{DL}$ is
 551 the *Information Gain* function [14, 20, 24, 57]. Specifically, given a fuzzy
 552 $\mathcal{EL}(\mathbf{D})$ GCI ϕ of the form $C \sqsubseteq T$ chosen at the previous step, a KB $\mathcal{K}$, a set
 553 of positive examples Pos still to be covered and a candidate fuzzy $\mathcal{EL}(\mathbf{D})$
 554 GCI ϕ' of the form $C' \sqsubseteq T$, then

$$gain(\phi', \phi, \mathcal{K}, Pos) = p * (\log_2(cf(\phi', \mathcal{K}, Pos)) - \log_2(cf(\phi, \mathcal{K}, Pos))) \quad (\text{A.1})$$

555 where $p = |C' \sqcap C|_{\mathcal{K}}^{Pos}$ is the fuzzy cardinality of positive examples in Pos
 556 covered by ϕ that are still covered by ϕ' .

⁴ $\mathbf{A}_{\mathcal{K}}$ is the set of all atomic concepts in $\mathcal{K}$, $\mathbf{R}_{\mathcal{K}}$ is the set of all object properties in $\mathcal{K}$, $\mathbf{S}_{\mathcal{K}}$ is the set of all numeric datatype properties in $\mathcal{K}$, $\mathbf{B}_{\mathcal{K}}$ is the set of all boolean datatype properties in $\mathcal{K}$ and $\mathcal{D}$ a set of (fuzzy) datatypes.

Algorithm 3 LEARN-ONE-AXIOM

Input: KB $\mathcal{K}$, target concept name T , set Pos of positive examples still to be covered, training sets P, N, U of positive, negative and unlabelled examples, respectively, confidence threshold $\theta \in [0, 1]$, non-positive coverage percentage $\eta \in [0, 1]$

Output: A fuzzy $\mathcal{EL}(\mathbf{D})$ GCI of the form $C \sqsubseteq T$

```
1:  $NP \leftarrow N \cup U;$  ▷ Note:  $NP$  are the non-positives
2:  $C \leftarrow \top;$  ▷ Start from  $\top$ 
3:  $\phi \leftarrow C \sqsubseteq T;$ 
4: while  $C \neq \text{null}$  do
  ▷ Loop until no improvement
5:    $C_{best} \leftarrow C;$ 
6:    $maxgain \leftarrow 0;$ 
7:    $\mathcal{C} \leftarrow \rho(C);$  ▷ Compute all refinements of  $C$ 
  ▷ Compute the score of the refinements and select the best one
8:   for all  $C' \in \mathcal{C}$  do
9:      $\phi' \leftarrow C' \sqsubseteq T;$ 
10:     $gain \leftarrow gain(\phi', \phi, \mathcal{K}, Pos);$ 
11:    if ( $gain > maxgain$ ) then
12:       $maxgain \leftarrow gain;$ 
13:       $C_{best} \leftarrow C';$ 
14:    if  $C_{best} = C$  then ▷ No improvement
  ▷ Stop if the confidence degree is above the threshold or the non-positive coverage is below the
  threshold
15:    if ( $cf(C_{best} \sqsubseteq T, \mathcal{K}, P) \geq \theta$ ) and  $supp(C_{best} \sqsubseteq T, \mathcal{K}, NP) \leq \eta$  then break;
16:     $C \leftarrow C_{best};$ 
17:     $\phi \leftarrow C \sqsubseteq T;$ 
18: return  $\phi;$ 
```

557 *The LEARN-ONE-AXIOM algorithm.* The LEARN-ONE-AXIOM algorithm (see,
558 *e.g.* [14, 20, 24]) is illustrated in Algorithm 3: lines 1 - 3 are simple initiali-
559 sation steps. Please note here that NP are the non-positives (see Remark 1),
560 which states that we will distinguish among positives and non-positives only
561 (*cf.* also line 15, where the non-positive coverage percentage is used). Steps
562 4-18 are the main loop from which we may exit if the stopping criterion is
563 satisfied, in step 7 we compute all new refinements, which are then scored
564 in steps 8-13 and update the best one. At the end of the algorithm, once
565 we exit from the main loop, the best-found GCI is returned (step 19). The
566 LEARN-ONE-AXIOM algorithm stops when the confidence degree is above a
567 given threshold $\theta \in [0, 1]$ and the non-positive coverage percentage is below
568 $\eta \in [0, 1]$, or no GCI can be learnt anymore.

569 References

- 570 [1] OWL 2 Web Ontology Language Document Overview,
571 <https://www.w3.org/TR/owl2-overview/> (2012).
- 572 [2] F. Baader, D. Calvanese, D. L. McGuinness, D. Nardi, P. F. Patel-Schneider, The

- 573 Description Logic Handbook: Theory, Implementation and Applications, 2nd Edition,
574 Cambridge University Press, 2007.
- 575 [3] F. Bobillo, M. Cerami, F. Esteva, À. García-Cerdàña, R. Peñaloza, U. Straccia, Fuzzy
576 description logics, in: Handbook of Mathematical Fuzzy Logic, Volume 3, 2015, Ch.
577 XVI, pp. 1105–1181.
- 578 [4] U. Straccia, Foundations of Fuzzy Logic and Semantic Web Languages, Chapman &
579 Hall/CRC, 2013.
- 580 [5] F. Bobillo, U. Straccia, Fuzzy ontology representation using OWL 2, International
581 Journal of Approximate Reasoning 52 (2011) 1073–1094.
- 582 [6] L. D. Raedt, K. Kersting, Statistical relational learning, in: Encyclopedia of Machine
583 Learning and Data Mining, 2017, pp. 1177–1187.
- 584 [7] F. A. Lisi, Logics in machine learning and data mining: Achievements and open
585 issues, in: Proc. of the 34th Italian Conference on Computational Logic, Trieste,
586 Italy, June 19-21, 2019., Vol. 2396 of CEUR Workshop Proc., 2019, pp. 82–88.
- 587 [8] A. Rettinger, U. Lösch, V. Tresp, C. d’Amato, N. Fanizzi, Mining the semantic
588 web - statistical learning for next generation knowledge bases, Data Mining and
589 Knowledge Discovery 24 (3) (2012) 613–662.
- 590 [9] R. C. Agarwal, M. V. Joshi, PNRule: A new framework for learning classifier models
591 in data mining (a case-study in network intrusion detection), in: Proc. of the 2001
592 SIAM International Conference on Data Mining (SDM), 2001, pp. 1–17.
- 593 [10] R. C. A. Mahesh V. Joshi, V. Kumar, Predicting rare classes: can boosting make any
594 weak learner strong?, in: Proc. of the Eighth ACM SIGKDD International Conference
595 on Knowledge Discovery and Data Mining, 2002, pp. 297–306.
- 596 [11] P. Hájek, Making fuzzy description logics more general, Fuzzy Sets and Systems
597 154 (1) (2005) 1–15.
- 598 [12] G. J. Klir, B. Yuan, Fuzzy sets and fuzzy logic: theory and applications, Journal of
599 Chemical Information and Computer Sciences (1996) 619–619.
- 600 [13] J. C. Bezdek, Pattern Recognition with Fuzzy Objective Function Algorithms,
601 Springer New York, NY, 1981.
- 602 [14] F. A. Cardillo, U. Straccia, Fuzzy OWL-BOOST: Learning fuzzy concept inclusions
603 via real-valued boosting, Fuzzy Sets and Systems 438 (2022) 164–186.
- 604 [15] I. Huitzil, U. Straccia, N. Díaz-Rodríguez, F. Bobillo, Datil: Learning fuzzy ontology
605 datatypes, in: Information Processing and Management of Uncertainty in Knowledge-
606 Based Systems. Theory and Foundations, 2018, pp. 100–112.

- [16] F. Bobillo, U. Straccia, Aggregation operators for fuzzy ontologies, *Applied Soft Computing* 13 (9) (2013) 3816–3830.
- [17] V. Torra, Y. Narukawa, *Modeling Decisions: Information Fusion and Aggregation Operators*, Springer Berlin, Heidelberg, 2007.
- [18] U. Straccia, Reasoning within fuzzy description logics, *Journal of Artificial Intelligence Research* 14 (2001) 137–166.
- [19] F. A. Lisi, U. Straccia, Learning in description logics with fuzzy concrete domains, *Fundamenta Informaticae* 140 (3-4) (2015) 373–391.
- [20] U. Straccia, M. Mucci, pFOIL-DL: Learning (fuzzy) $\mathcal{EL}$ concept descriptions from crisp OWL data using a probabilistic ensemble estimation, in: *Proc. of the 30th Annual ACM Symposium on Applied Computing (SAC-15)*, 2015, pp. 345–352.
- [21] P. Westphal, L. Böhmann, S. Bin, H. Jabeen, J. Lehmann, SML-bench - A benchmarking framework for structured machine learning, *Semantic Web* 10 (2) (2019) 231–245.
- [22] F. Bobillo, U. Straccia, *The fuzzy ontology reasoner fuzzyDL* (2016).
URL <https://www.umbertostraccia.it/cs/software/fuzzyDL/fuzzyDL.html>
- [23] F. Bobillo, U. Straccia, Reasoning within fuzzy OWL 2 EL revisited, *Fuzzy Sets and Systems* 351 (2018) 1–40.
- [24] F. A. Lisi, U. Straccia, A logic-based computational method for the automated induction of fuzzy ontology axioms, *Fundamenta Informaticae* 124 (4) (2013) 503–519.
- [25] F. Bobillo, U. Straccia, *Fuzzydl-learner* (2016).
URL <http://www.umbertostraccia.it/cs/software/FuzzyDL-Learner/>
- [26] D. Dua, C. Graff, *UCI Machine Learning Repository* (2017).
URL <http://archive.ics.uci.edu/ml>
- [27] P. Svec, S. Balogh, M. Homola, Experimental evaluation of description logic concept learning algorithms for static malware detection, in: *Proc. of the 7th International Conference on Information Systems Security and Privacy*, 2021, pp. 792–799.
- [28] L. Badea, S. Nienhuys-Cheng, A refinement operator for description logics, in: *Inductive Logic Programming*, 2000, pp. 40–59.
- [29] M. Chitsaz, K. Wang, M. Blumenstein, G. Qi, Concept learning for $\mathcal{EL}^{++}$; by refinement and reinforcement, in: *PRICAI 2012: Trends in Artificial Intelligence*, 2012, pp. 15–26.
- [30] C. d’Amato, Machine learning for the semantic web: Lessons learnt and next research directions, *Semantic Web* 11 (1) (2020) 195–203.

- [31] J. Lehmann, P. Hitzler, Foundations of Refinement Operators for Description Logics, in: Inductive Logic Programming, 2008, pp. 161–174.
- [32] J. Lehmann, P. Hitzler, Concept learning in description logics using refinement operators, Machine Learning 78 (2010) 203–250.
- [33] F. A. Lisi, D. Malerba, Ideal refinement of descriptions in AL-Log, in: Inductive Logic Programming, 2003, pp. 215–232.
- [34] M. Serrurier, H. Prade, Improving expressivity of inductive logic programming by learning different kinds of fuzzy rules, Soft Computing 11 (2007) 459–466.
- [35] M. E. Cintra, M. C. Monard, H. de Arruda Camargo, On rule learning methods: A comparative analysis of classic and fuzzy approaches, in: Soft Computing: State of the Art Theory and Novel Applications, 2013, pp. 89–104.
- [36] M. Drobics, U. Bodenhofer, E.-P. Klement, FS-FOIL: an inductive learning method for extracting interpretable fuzzy descriptions, International Journal of Approximate Reasoning 32 (2-3) (2003) 131–152.
- [37] D. Shibata, N. Inuzuka, S. Kato, T. Matsui, H. Itoh, An induction algorithm based on fuzzy logic programming, in: Methodologies for Knowledge Discovery and Data Mining, 1999, pp. 268–274.
- [38] N. Fanizzi, G. Rizzo, C. d’Amato, F. Esposito, DLFoil: Class expression learning revisited, in: Knowledge Engineering and Knowledge Management, 2018, pp. 98–113.
- [39] G. Rizzo, N. Fanizzi, C. d’Amato, Class expression induction as concept space exploration: From DL-Foil to DL-Focl, Future Generation Computing Systems 108 (2020) 256–272.
- [40] N. Fanizzi, G. Rizzo, C. d’Amato, Boosting DL concept learners, in: The Semantic Web, 2019, pp. 68–83.
- [41] M. J. del Jesús, F. Hoffmann, L. J. Navascués, L. Sánchez, Induction of fuzzy-rule-based classifiers with evolutionary boosting algorithms, IEEE Trans. Fuzzy Syst. 12 (3) (2004) 296–308.
- [42] J. Otero, L. Sánchez, Induction of descriptive fuzzy classifiers with the logitboost algorithm, Soft Computing 10 (9) (2006) 825–835.
- [43] A. M. Palacios, L. Sánchez, I. Couso, Using the AdaBoost algorithm for extracting fuzzy rules from low quality data: Some preliminary results, in: IEEE International Conference on Fuzzy Systems, 2011, pp. 1263–1270.
- [44] L. Sánchez, J. Otero, Boosting fuzzy rules in classification problems under single-winner inference, International Journal of Intelligent Systems 22 (9) (2007) 1021–1034.

- 677 [45] H.-y. Zhu, Y. Ding, H. Gao, W. Liu, Fuzzy prediction in classification of AdaBoost
678 algorithm, in: International Conference on Oriental Thinking and Fuzzy Logic, Vol.
679 443 of Advances in Intelligent Systems and Computing, 2016, pp. 129–136.
- 680 [46] S. Bloehdorn, Y. Sure, Kernel methods for mining instance data in ontologies, in:
681 The Semantic Web, Vol. 4825, 2007, pp. 58–71.
- 682 [47] N. Fanizzi, C. d’Amato, F. Esposito, Induction of robust classifiers for web ontologies
683 through kernel machines, Journal of Web Semantics 11 (2012) 1–13.
- 684 [48] F. Nicola, C. d’Amato, E. Floriana, Towards the induction of terminological decision
685 trees, in: Proc. of the 2010 ACM Symposium on Applied Computing, 2010, pp.
686 1423–1427.
- 687 [49] G. Rizzo, C. d’Amato, N. Fanizzi, F. Esposito, Tree-based models for inductive clas-
688 sification on the web of data, Journal of Web Semantics 45 (2017) 1–22.
- 689 [50] G. Rizzo, N. Fanizzi, C. d’Amato, F. Esposito, Approximate classification with web
690 ontologies through evidential terminological trees and forests, International Journal
691 of Approximate Reasoning 92 (2018) 340–362.
- 692 [51] P. Minervini, C. d’Amato, N. Fanizzi, Learning probabilistic description logic con-
693 cepts: Under different assumptions on missing knowledge, in: Proc. of the 27th
694 Annual ACM Symposium on Applied Computing, 2012, pp. 378–383.
- 695 [52] M. Zhu, Z. Gao, J. Z. Pan, Y. Zhao, Y. Xu, Z. Quan, Tbox learning from incomplete
696 data by inference in BelNet+, Knowledge-Based Systems 75 (2015) 30–40.
- 697 [53] J. Lehmann, Hybrid learning of ontology classes, in: Machine Learning and Data
698 Mining in Pattern Recognition, 2007, pp. 883–898.
- 699 [54] M. Nickles, A. Rettinger, Interactive relational reinforcement learning of concept
700 semantics, Machine Learning 94 (2) (2014) 169–204.
- 701 [55] G. Rizzo, C. d’Amato, N. Fanizzi, An unsupervised approach to disjointness learning
702 based on terminological cluster trees, Semantic Web 12 (3) (2021) 423–447.
- 703 [56] U. S. Fernando Bobillo, The fuzzy ontology reasoner *fuzzyDL*, Knowledge-Based Sys-
704 tems 95 (2016) 12 – 34.
- 705 [57] F. A. Lisi, U. Straccia, Dealing with incompleteness and vagueness in inductive logic
706 programming, in: 28th Italian Conference on Computational Logic (CILC-13), Vol.
707 1068, 2013, pp. 179–193.